

OMS Model FT20 Semi-Automatic Shrink Wrapper

- Ideal for Wrapping Small Volumes
- Hot Air System (no flame)
- Energy Saving Operation
- Auto Gas Shut Off-Feature

Features and Benefits

Hot Air System (No Flame)

Hot air is emitted from innovative gas burners with no flame.



Optimized Shrink System

Special air combustion compartment inside the burner ensures excellent flame stability and optimised heat shrinkage whatever the external environmental conditions.

Energy Saving Operation

Flame is only ignited during wrapping operation ensuring considerable energy saving.

Automatic Gas Cut Off

Should ignition be interrupted or the heating ring fail to switch on, the automatic flame sensor immediately stops gas delivery.

Flame Control System with Safety Valves

Gas burners are individually equipped with flame control systems and safety electro-valves thereby avoiding the risk of unburned gases escaping.

Height Detection Photocell

Automatic pallet height detection saves time.

Health and Safety Benefits

Semi-automatic system reduces the risk of Repetitive Strain Injury to the Operator.

Optional Equipment

Remote Control, 1800mm Diameter Turntable, Higher Column, Soft-Start (for heavy loads), Ramp.

Gases used	LPG, Natural Gas, Propane
Gas Pressure	200mbar
Gas Consumption	0.10Nm ³ (based on Standard Pack Dims and 130 micron film)
Thermoshrink Cycle Time	150-160sec
Standard Pack Dims	1000 x 1200 x H1200mm
Standard Turntable Diameter	1500mm
Standard Turntable Load	1200kg
Power	2kw
Power Supply	400-415V, 3Ph – 50/60Hz

Dimensions and specifications are subject to change without notice.