

OMS Model M-10 B Vertical Strapping Machine

- Vertically straps a wide variety of baled waste products
- Can be fitted to new or existing waste balers
- Designed to ensure protection from debris ingress
- 200,000 cycles between major services with OMS Strapping Heads



Features and Benefits

Debris Ingress Protection

The machine has been specially designed to ensure protection from debris ingress.

Easy Maintenance

The machine has been designed to ensure that the strapping head can easily be accessed for maintenance.

Proven & Reliable Heat Seal Strapping Heads

OMS TR Series Heads only require major service every 200,000 cycles.

Fast, Consistent Strap Feed

Precise, repeatable strap feeding avoids jams and increases up-time.

Strap Coil Holder Options

Options include Tower, Scissor and Jumbo Coil Holders, all with auto recovery to ensure strap is taut and controlled.

Strap/ Coil Options	Polyester or Polypropylene ID 406mm x W 150mm
Strap Width	8-19mm dependent on head
Strap Thickness	0.5- 1.3mm dependent on head
Cycle Time	Depends on head, strap and arch size
Strap Tension	0 to 700kg dependent on head
Tensioning Speed	0.25m/sec
Strap feed + recovery speed	2.5 or 5.5m/sec
Power Supply	400-415V, 3Ph – 50/60Hz

Dimensions and specifications are subject to change without notice.