

# OMS Model M-10 Vertical Strapping Machine

- Vertically straps a wide variety of conveyed products
- Inverted, Fixed Strapping Head and Fixed Arch
- Compact dimensions facilitate integration in tight spaces
- 200,000 cycles between major services with OMS Strapping Heads



## Features and Benefits

### Integral Rollers on Top Plate of Strapping Head

Packs can easily be moved through the arch from one conveyor to the other.

### Proven & Reliable Heat Seal Strapping Heads

OMS TR Series Heads only require servicing every 200,000 cycles.

### Fast, Consistent Strap Feed

Precise, repeatable strap feeding avoids jams and increases up-time.

### Strap Coil Holder Options

Options include Tower, Scissor and Jumbo Coil Holders, all with auto recovery to ensure strap is taut and controlled.

### Optional Equipment

Pedestal or Desk Control Panel, Driven Conveyors, Centering Device.

### Safety Guarding Options

Gordian can offer a full perimeter safety guarding system in partnership with our safety system suppliers.

|                             |   |
|-----------------------------|---|
| Strap/ Coil Options         | Polyester or Polypropylene ID 406mm x W 150mm |
| Strap Width                 | 9-19mm dependent on head                      |
| Strap Thickness             | 0.5- 1.3mm dependent on head                  |
| Cycle Time                  | Depends on head, strap and arch size          |
| Strap Tension               | 0 to 700kg dependent on head                  |
| Tensioning Speed            | 0.25m/sec                                     |
| Strap feed + recovery speed | 2.5 or 5.5m/sec                               |
| Power Supply                | 400-415V, 3Ph – 50/60Hz                       |

*Dimensions and specifications are subject to change without notice.*